

# D-SUB connector

## Connects stably, enjoys data transmission

D-SUB connector is named because of its unique D-shaped shield shape. Capable of protecting connectors and matching and docking them.

DEGSON D-SUB connector, complete specifications, diversified series products for you to choose from!



OFFICIAL WEBSITE



LINKEDIN



Needle D-SUB



Punching needle D-SUB



Anti-type D-SUB



Double-layer D-SUB



Hybrid D-SUB

### Product features

- Punching/turning two gong arts
- Two angles of straight seat/curved seat
- Double-layer compact design
- Waterproof design
- Use a hybrid design

### Technical specifications

|                                       |               |                         |                                   |
|---------------------------------------|---------------|-------------------------|-----------------------------------|
| Standard D-sub product pin number     | 9, 15, 25Pin  | Working temperature     | -40 to 105°C                      |
| High-density D-sub product pin number | 15, 26, 44Pin | Contact material        | Copper/phosphorus copper          |
| Rated current                         | 3.0AMP        | Contact coating         | Au or Sn                          |
| Maximum contact resistance            | 20mΩ          | Plastic flame retardant | UL94 V-0                          |
| Insulance                             | 1000MΩ        | Shell                   | Cold rolled steel, nickel plating |
| Voltage withstand                     | 500V AC/min   | Screw                   | Copper/steel screw                |

### Color customization

Multiple color choices



### Application industry

Product application-industrial equipment



#### New energy

- Energy storage BMS
- Inverter control board
- Charging pile control panel



#### Factory automation

- PLC controller
- Servo control device
- Human-Machine Interface

